

EmssRobot®

Tostaer



Web : www.emssrobot.com

Mail : info@emssrobot.com

Tosstoer

Edge rollers for flat ground parking.

Special shaped handle for easy flat ground parking.

Intelligent control valve.

Quick release and thrust lift/lowering device.

Hydraulic pressure for the maximum lifting possibility.

Strong powerful hydraulic motor.

Front loading device.

Longer fork / longer steel control arms.



Platform folding

Folding/opening the platform in one second.

Flat ground parking (without tilting device).



Foldable Flat-Ground Working/Brace

Working on temporary ground is easier.



Intelligent Control System

Speed regulation | Go up/down | Switch | Battery display.

Telescopic pull rod makes it easier to carry goods.

Certifications

EN 12158:2015 + A1:2016

EN 12158:2015 + A1:2016

EN 12158:2015 + A1:2016

EN 12158:2015 + A1:2016

EN 12158:2015 + A1:2016

EN 12158:2015 + A1:2016

EN 12158:2015 + A1:2016

Grade Of Waterproof

IP54



Unfolded Size/ Folded Size / Packaging Size

1180mmx1120mmx1210* (mm)

1180mmx1120mmx1210* (mm)

1180mmx1120mmx1210* (mm)

Net Weight / Gross Weight / Maximum Load

200KG / 200KG / 200KG

Adjustment Range Of Pull Rod (Up/ Down)

0-17 (mm)

Support Arm Angle / Support Arm Length

90° / 2400 (mm)

Charge Height Range

7-11.80 (mm)

Feasible Charge Size Range / Length / Width / Height

Length > 420 / Width > 420 / Height > 1180 (mm)

Clear Plate Rotation Angle Range (Horizontal / Backward)

0° - 180° / 0° - 180°

Platform Material / Platform

Aluminum Alloy Square Tube / 10 (mm)

Platform Size / Length / Width

4117x280 (mm)

Support Arm Material / Braking System / Braking Angle

Iron / 0°

Wheel Size (F / R)

10寸x4 / 10寸x4

Motor / Type / Voltage / Power

Brushless Motor / 48V / 400W

Battery / Type / Voltage / Capacity

Lithium / 48V / 17.4Ah

Speed Control / Climb Speed

Brushless Motor / 18 Steps / Min

Maximum / Minimum Angle

0-180°

Minimum Turning Radius

1000 (mm)

Time / Charger / Charge / Service Life

4.5H / 1.5H / 4000H / 1 Year / 500 Recharges

Temperature (Use / C) / Storage / C

0-40 / -10-40 (Dry Environment)

Sound Decibel / Working Time

<70

Grade Of Waterproof

IP54



EmssRobot®
Tostor



Jiangsu Emss Robot Equip. Co., Ltd.

Jiangsu Emss Robot Equip. Co., Ltd.

<http://www.emssrobot.com>

TEL: 0511-85111111
EMAIL: emssrobot@emssrobot.com
WWW.EMSSROBOT.COM